







SPECIFICATION SHEET WWW.CONEN-SYSTEMS.COM

## PROJECTION SCREEN WITH ROBUST CHASSIS - "CARAT

W/H: 300X250 CM, WITH CRANK HANDLE



## PRODUCT

Mobile projection screens are the ideal solution if the furnishings do not allow a fixed installation or if a quick and easy presentation set-up is required in possibly different premises. Optimal at trade fairs, in churches, conference or training rooms .

The standard color of the aluminum housing (W 19 x H 19 cm) and the chassis are RAL 9016 Traffic White. Other colors are optional according to RAL Classic, please contact us!

You can choose between a motor or crank drive. The drive is located on the right side from projection direction and the lid can be operated manually. The optimal flatness is guaranteed by the robustly designed scissor joints.

Due to the four easy-running rollers of the chassis, the projection screen is mobile and flexible in use at any time.





## FEATURES

- Formats up to 350x300 cm, bottom edge of the picture at 80 cm
- Picture wall surface Polar GS flame retardant, meets the requirements of DIN 4102 - B1
- Construction DIN 56950-4: 2015 Safety requirements and tests for prefabricated picture walls



Accessories

| ltem number | 18112528                                   |                    |
|-------------|--|--------------------|
| Image size  | 3000 mm - 2500 mm                          | 118.1" - 98.4"     |
| Weight      | 145 kg                                     | 319.7 lbs          |
| Packages    | Package dimensions WxHxD                   | Package weight     |
| 18112528    | 3450 x 900 x 930 mm / 135.8 x 35.4 x 36.6" | 150 kg / 330.7 lbs |

Conen Systems GmbH

T E +49 5251 50012-0

Conenstr. 4 54497 Morbach-Gonzerath Germany

sales@conen-systems.com

www.conen-systems.com

© Copyright by Conen Systems GmbH

02/19/2025 Page 2/2

Conen Systems GmbH is not responsible for printing errors. Conen Systems GmbH reserves the right to change or modify pricing and product specifications with or without prior notification. Illustrations may not be exactly as shown. No parts may be reproduced by any means without prior authorization of Conen Systems GmbH. All rights reserved 2025.